

# The Apache Forrest xdocs document-v2.0 DTD

## This is a subtitle

SVN: \$Revision\$ \$Date\$

Example

by Joe Bloggs, Fred Bloggs

---

NOTICE: The content of this document doesn't make any sense at all.

---

*This is a demonstration document using all possible elements  
in the current Apache Forrest xdocs document-v20.dtd*

Forrest, Apache, example document

## Table of contents

1 Sample Content.....	2
1.1 Block and inline elements.....	2
1.2 Various presentation formats.....	4
1.3 Using sections.....	4
1.4 Sections, the sequel.....	5
1.5 Showing preformatted source code.....	5
1.6 Using tables.....	5
1.7 Using figures.....	6
1.8 Using map and area.....	6
1.9 Using class attribute on links.....	7
2 DTD changes.....	7
2.1 Changes between document-v13 and document-v20.....	7
2.2 Changes between document-v12 and document-v13.....	7
2.3 Changes between document-v11 and document-v12.....	7

---

This is a legal notice, so it is **important**.

Copyright © 2002 The Apache Software Foundation. Licensed under Apache License 2.0 All rights reserved.

**Note:**

This is a demonstration document using all possible elements in the current Apache Forrest xdocs document-v2.0.dtd (See the [DTD changes](#) section at the bottom.)

## 1 Sample Content

---

**Hint:** See the xml source to see how the various elements are used and see the [DTD reference documentation](#).

### 1.1 Block and inline elements

---

This is a simple paragraph. Most documents contain a fair amount of paragraphs. Paragraphs are called `<p>`.

With the `<p xml:space="preserve">` attribute, you can declare that whitespace should be preserved, without implying it is in any other way special.

This next paragraph has a class attribute of 'quote'. CSS can be used to present this `<p class='quote'>` in a different style than the other paragraphs. The handling of this quoted paragraph is defined in the `<extra-css>` element in the `skinconf.xml`.

*Anyway, like I was sayin', shrimp is the fruit of the sea. You can barbecue it, boil it, broil it, bake it, sautee it. Dey's uh, shrimp-kabobs, shrimp creole, shrimp gumbo. Pan fried, deep fried, stir-fried. There's pineapple shrimp, lemon shrimp, coconut shrimp, pepper shrimp, shrimp soup, shrimp stew, shrimp salad, shrimp and potatoes, shrimp burger, shrimp sandwich. That- that's about it.*

A number of in-line elements are available in the DTD, we will show them inside an unordered list (`<ul>`):

- Here is a simple list item (`<li>`).
- Have you seen the use of the `<code>` element in the previous item?
- Also, we have `<sub>` and `<sup>` elements to show content <sup>above</sup> or <sub>below</sub> the text baseline.
- There is a facility to *emphasize* certain words using the `<em>``<strong>` elements.
- We can use  `<icon>`s too.
- Another possibility is the `<img>` element: 

, which offers the ability to refer to an image map.

- We have elements for hyperlinking:

`<a href=" ../index.html ">`

Use this to [link](#) to another document. As per normal, this will open the new document in the same browser window.

`<a href="#section">`

Use this to [link](#) to the named anchor in the current document.

`<a href=" ../index.html#status ">`

Use this to [link](#) to another document and go to the named anchor. This will open the new document in the same browser window.

**Targetted window control with jump and fork.**

See demonstration [using class attribute on links](#).

- Oh, by the way, a definition list `<dl>` was used inside the previous list item. We could put another
  - unordered list
  - inside the list item

Or even tables..	inside tables..
or inside lists, but I believe this liberty gets quickly quite hairy as you see.	

Table 1: A sample nested table

So far for the in-line elements, let's look at some paragraph-level elements.

<b>FIXME ( SN):</b>
The <code>&lt;fixme&gt;</code> element is used for stuff which still needs work. Mind the <code>author</code> attribute!
<b>Note:</b>
Use the <code>&lt;note&gt;</code> element to draw attention to something, e.g. ...The <code>&lt;code&gt;</code> element is used when the author can't express himself clearly using normal sentences ;-)
<b>Warning:</b>
Sleep deprivation can be the result of being involved in an open source project. (a.k.a. the <code>&lt;warning&gt;</code> element).
<b>Important</b>
If you want your own labels for notes and warnings, specify them using the <code>label</code> attribute.

Apart from unordered lists, we have ordered lists too, of course.

1. Item 1
2. Item 2
3. This should be 3 if my math is still OK.

## 1.2 Various presentation formats

---

This sample document, written in document-v20 XML can be presented via Forrest in a number of different formats. The links in the following list show this document in each of the currently available formats.

Each of the formats can be made available as a link near the top of the page. Actual placement of those links depends on the skin currently in use. Those links are enabled in the skinconf.xml via the `<disable-XXX-link>` elements in the skinconf.xml

Presentation Format	Description	skinconf.xml Element
<a href="#">HTML</a>	This document in HTML format.	Always generated by default. Cannot be turned off.
<a href="#">XML</a>	This document in its raw XML format.	<code>&lt;disable-xml-link&gt;</code> . By default, set to true, meaning that this link will not be shown.
<a href="#">PDF</a>	This document as Adobe PDF	<code>&lt;disable-pdf-link&gt;</code> . By default, set to false, meaning that this link will be shown.
<a href="#">Text</a>	<p>This document as straight text.</p> <p>For additional information see the Forrest text-output plugin.</p>	<code>&lt;disable-txt-link&gt;</code> . By default, set to true, meaning that this link will not be shown.
<a href="#">POD</a>	<p>This document as Perl POD (Plain Old Documentation). Text with minimal formatting directives. If on a *nix system with perl installed, see "man perlpod".</p> <p>For additional information see the Forrest pod-output plugin.</p>	<code>&lt;disable-pod-link&gt;</code> . By default, set to true, meaning that this link will not be shown.

## 1.3 Using sections

---

You can use sections to put some structure in your document.

## 1.4 Sections, the sequel

---

Just some second section.

### 1.4.1 Section 2.1

---

Which contains a subsection (2.1).

## 1.5 Showing preformatted source code

---

Enough about these sections. Let's have a look at more interesting elements, `<source>` for instance:

```
// This example is from the book _Java in a Nutshell_ by David Flanagan.
// Written by David Flanagan. Copyright (c) 1996 O'Reilly & Associates.
// You may study, use, modify, and distribute this example for any purpose.
// This example is provided WITHOUT WARRANTY either expressed or implied.

import java.applet.*;    // Don't forget these import statements!
import java.awt.*;

public class FirstApplet extends Applet {
    // This method displays the applet.
    // The Graphics class is how you do all drawing in Java.
    public void paint(Graphics g) {
        g.drawString("Hello World", 25, 50);
    }
}
```

CDATA sections are used within `<source>` elements so that you can write pointy brackets without needing to escape them with messy `&lt;` entities ...

```
<pointy>
  easy
</pointy>
```

Please take care to still use a sensible line-length within your source elements.

## 1.6 Using tables

---

And now for a table:

heading cell 1	heading cell 2	heading cell 3
data cell	this data cell spans two columns	
Tables can be nested:	column 1	column 2
	cell A	cell B
<ul style="list-style-type: none"> <li>• and can include most other elements</li> <li>• such as lists</li> </ul>		

Table 1: Table caption

## 1.7 Using figures


---

And a `<figure>` to end all of this. Note that this can also be implemented with an `<img>` element.



## 1.8 Using map and area

---



## 1.9 Using class attribute on links

---

The document-v13 had elements `<fork>` and `<jump>`. In document-v20, those elements no longer exist but the functionality can be duplicated by using the `@class` attribute. Even though the opening of separate windows should be under the control of the user, these techniques can still be employed.

Document V1.3	Document V2.0
<code>&lt;fork href="../index.html"&gt;</code>	<code>&lt;a class="fork" href="../index.html"&gt;</code>
<code>&lt;jump href="../index.html"&gt;</code>	<code>&lt;a class="jump" href="../index.html"&gt;</code>

## 2 DTD changes

---

See the generated [DTD reference documentation](#).

### 2.1 Changes between document-v13 and document-v20

---

- Renamed `<link>` to `<a>`
- Removed `<fork>` and `<jump>` in favour of the `<a>` element. See demonstration [using class attribute on links](#).
- Enabled use of XInclude. See example in the 'forrest seed sample' site.

### 2.2 Changes between document-v12 and document-v13

---

All v1.2 docs will work fine as v1.3 DTD. The main change is the addition of a `@class` attribute to every element, which enables the "extra-css" section in the skinconf to be put to good use.

### 2.3 Changes between document-v11 and document-v12

---

doc-v12 enhances doc-v11 by relaxing various restrictions that were found to be unnecessary.

- Links ((link|jump|fork) and inline elements (br|img|icon|acronym) are allowed inside title.
- Paragraphs (p|source|note|warning|fixme), table and figure|anchor are allowed inside li.
- Paragraphs (p|source|note|warning|fixme), lists (ol|ul|dl), table, figure|anchor are allowed inside definition lists (dd) and tables (td and dh).
- Inline content (strong|em|code|sub|sup|br|img|icon|acronym|link|jump|fork) is allowed in strong and em.

This is a legal notice, so it is **important**.